

PARUS LED grow light

PGL-E18(RBC) - Specification



Product	Model Name		PGL-E18	
	System Power Consumption		25°C 18Watt	
	Dimension		Ø120*136 mm	
	Packing(LxWxH)		125mm x 125mm x 143mm	
	Weight		0.31kg	
Power	AC input voltage range		Free voltage 85~285VAC, 50~60Hz	
	SMPS mode (ballast)		DC Current Design(C.C Mode)	
	Protection		Short circuit, Overload, Over voltage	
	Power Factor		Over 85%, PFC >0.9	
LEDs	Ratio(R:B:O)		(5:2:2)	
	Light source		Hi-Power 700mA LED	
	Total number of LED's		9EA	
	Used LED		Hi-power Grow LED	
	RED	Number of LED's		5ea
		Type of LED		2 watt Hipower Grow LED
		Peak Wavelength		635nm, 665nm
		Dominant Wavelength		630nm, 660nm
	Blue	Number of LED's		2ea
		Type of LED		2 watt Hi-power LED
		Peak Wavelength		435nm
		Dominant Wavelength		445nm
	UV	Number of LED's		
		Type of LED		
		Peak Wavelength		
Dominant Wavelength				
Infrared	Number of LED's			
	Type of LED			
	Peak Wavelength			
	Dominant Wavelength			
Other	Number of LED's		2ea(white)	
	Type of LED		2 watt Hi-power LED	
	Peak Wavelength		450nm	
	Dominant Wavelength		465nm	
Heat Sink	Heat Sink Type		Cooling by free air convention	
	FRAME Metrial	Body	Aluminium	
		PCB	Metal PCB(aluminium)	
		Heat conduction	1.8 w/m.k	
		Thermal resistance	0.18 °C/w	
IP Class	IP52			
Efficiency	PPFD			
Ambient Temperature	Storage Temp.	-30°C ~ 85°C		
	Operation Temp.	~35°C		
Angle	Lamp angle	60°		
Life time	Over 50,000hr			
Safety	Standard	CE, EMC		
Warranty	2 year	2 year		

PARUS LED Grow light Wavelength

